

19.2 AGIECUT HSS

ED wire cutting machine
AGIECUT HSS

1X0,
150F,
150P

2X0

3X0

Dimension

External dimensions	width	2325	2170	2150	mm
① with STARTRON (option)	depth	1620	1740	2400	mm
	height	2140	2192/2490①	2805	mm
Net weight of the system		2910	3960	7695	kg
Max. workpiece dimensions	width	810	860	1100	mm
	depth	580	530	1300	mm
	height	250	250	400	mm
Clamping surface	width	560	680	1100	mm
	depth	445	500	1008	mm
Axis travel	X axes	300	400	700	mm
	Y axes	200	250	400	mm
	Z axes	251	251	406	mm
Max. workpiece weight					
- Submerged		200	400	2000	kg
- Not submerged		550	850	3000	kg
AGIECONIC					
- Axis travel	U axes	<	± 30	>	mm
	V axes	<	± 30	>	mm
- Max. taper/height		<	± 30/7	>	degr./mm
AGIEJET automatic wire threading					
- Min. Start hole		<	∅ 2,0	>	mm
- Max. threadable workpiece-height		250	250	400 *	mm
Wire supply					
- Wire diameter		<	0,1...0,3	>	mm
- Max. coil weight		<	16	>	kg
Work tank					
- Operating mode		Submerged or not submerged			

* 250 mm guaranteed